

CDR 252, CDR 352 & CDR 402

ø 250-400mm 11-13,5kg 0-45°

625mm







Fully aluminum drill stand combining rigidity, precision, ease of use and light weight. Unique accurate and smooth guiding thanks to 4 guiding rolls made of high performancy Nylon. Easily accessible guiding wheels for wear compensation adjustment.

Features	Benefits	
Aluminium column.	 Robust, reliable while light weight. 	
Rolls-guided carriage.	 High accurary drill guiding, few maintenance. 	
Laser pointer.	 For precise rig positioning. 	
Transport wheels (CDR352 & CDR402).	 For easy transportation (optional on CDR252). 	
3 points level adjustment.	 Quicker and faster installation. 	
Multi-purpose drive-lever.	 Can be used for levelling and locking screws. 	
Standard motor mounting fixture.	 Fits to most drilling motors on the market. 	
Transport handle on top.	 Easy and ergonomic handling. 	
Carriage travel (CDR402).	 2 different reports/ratio for an easy work. 	
Adjustable bit guide.	 Precise cutting of the bit. 	



Spirit level.



Transport wheels.



Laser pointer system.



Rolls-guided carriage.



DRILL RIGS

MODELS	CDR 252	CDR 352	CDR 402
Item No	3103 87341	3103 87342	3103 87343
EAN 13 Code	5450248 466727	5450248 466734	5450248 466741
TECHNICAL DATA			
Diam. Max	250mm	350mm	400mm
Hub	625mm	625mm	625mm
Column	Aluminum	Aluminum	Aluminum
Column section	55 x 60mm	70 x 70mm	70 x 70mm
Base	Dowel	Dowel	Dowel
Base dimensions	235 x 325mm	330 x 400mm	330 x 400mm
Bit guide	Yes	Yes	Yes
Motor mounting plate	Quick mounting plate incl.	Quick mounting plate incl.	Quick mounting plate incl.
Carriage	Aluminum	Aluminum	Aluminum
Carriage Guiding system	Rolls	Rolls	Rolls
Carriage handle	left-right	left-right	left-right
Carriage travel	1:1	1:1	1:1 + 1:5
Braces	Yes	Yes	Yes
Tilting	0-45°	0-45°	0-45°
Pointing laser	Yes	Yes	Yes
Spirit level	1	1	1
Transport wheels	Optional	Included	Included
Height	975mm	1050mm	1050mm
Weight	11kg	13kg	13,5kg



Simple level adjustment with 3 screws on base.



Optional vacuum plate especially designed for perfect and simple fitting with the base.
(310387431)



Unique precise and smooth guiding thanks to 4 guiding rolls made of high performance Nylon. Easily accessible guiding wheels for wear compensation adjustment.